

XTAR D30 6000 Diving Flashlight

Light Wide, Capture All



ANSI	Flood
	High
Luminance	6000lm
Runtime	45 minutes
CRI	>90
CCT	5000K
Beam Angle	140°
Beam Throw	89m
Impact Resistance	1.5m
Depth Rating	Underwater 100m
Lamp Bead	Cree LED
Switch Type	Magnetic press button switch with lock
Size	φ62mm(head)x 157mm(length)
Net Weight	610g (excluding battery)
Package Contents	D30 6000, Batteries, Charger, Adapter, Cable, Joint ball, O-ring, Lanyard, Manual

Notes:

- 1) Above data is derived from XTAR Lab, and tested base on 4 x protected 18650 3600mAh batteries.
- 2) Please use batteries with max continuous discharge current 10A, such as XTAR 18650 3500mAh & 18650 3600mAh batteries.

Product advantage:

- 6000lm consistent output ensures never miss a moment.
- 45 minutes runtime with four protected 18650 3600mAh batteries.
- 140° extra-wide beam angle offers maximum visibility.
- With CRI rating of over 90, CCT of 5000K, and the imported Cree LEDs to restore natural colors.
- Magnetic press button switch with lock to prevent accidental power-on.
- LED low power indicator prevents unexpected power outages.
- Protection against reverse polarity prevents incorrect battery insertion.
- 1/4" ball mount for easy video-system mounting.
- Advanced Al6063 with Class III hard anodized finish provides wear resistance and corrosion resistance.

Tips:

- 1) When the battery is depleted or flashlight is not in use for a long time, please take out the battery.
- 2) Please use protected 18650 Li-ion battery for the flashlight.
- 3) Please do not wipe the battery with any corrosive material.
- 4) Please note the battery polarity when installing the battery, ensuring the positive pole towards the flashlight head.
- 5) Please do not use the flashlight on land for prolonged periods of time, as it will become hot and may cause burns upon touch.

Important Notice

This data sheet contains typical information specific to flashlights manufactured at the time of its publication.

Contents herein do not constitute a warranty.

©XTAR - All Rights Reserved